



RHINO Floodlight



PRODUCT OVERVIEW

The **Rhino Flood Light** is a very versatile and affordable floodlight, designed to withstand extreme weather conditions whilst delivering a powerful punch for its size. Equipped with a Meanwell power supply and Phillips or Osram LED chipsets and is extremely effective in keeping the chipset temperature to an absolute minimum, thereby ensuring maximum life time.

The **Rhino Floodlight** has an expected lifespan of > 50, 000 hours. Installation is easy and the luminaire is virtually maintenance free. Multiple beam angles are available which makes this luminaire suitable for almost any application.

Quality comes standard...



Hours
LIFESPAN



IP66
INDOOR



Low
MAINTENANCE



Year
WARRANTY



BEE
LEVEL ONE



Product
CERTIFICATION

APPLICATIONS

Industrial Areas

Workshops

Commercial Areas

Store Rooms

Warehouses

Logistic Centres

FEATURES

Water, Dust, Damp & Pressure Proof

Lifespan: >50, 000hrs

High Luminous Efficiency (120lm/W)

CRI: >80

Excellent heat dissipation

Input Voltage: 100-277VAC

Easy Installation

Power Factor: >0.98

Warranty: 5 Years

Various Beam Angles

Rhino Floodlight



TECHNICAL DATA

MODEL No.:	POWER (W)	LUMEN (lm/W)	BEAM ANGLE	CCT (K)
KIN/35*/**	35	120/150	30°/60°/90°/80°x140°	2700-6500
KIN/50*/**	50	120/150	30°/60°/90°/80°x140°	2700-6500
KIN/75*/**	75	120/150	30°/60°/90°/80°x140°	2700-6500
KIN/100*/**	100	120/150	30°/60°/90°/80°x140°	2700-6500
KIN/120*/**	120	120/150	30°/60°/90°/80°x140°	2700-6500
KIN/150*/**	150	120/150	30°/60°/90°/80°x140°	2700-6500
KIN/200*/**	200	120/150	30°/60°/90°/80°x140°	2700-6500
KIN/300*/**	300	120/150	30°/60°/90°/80°x140°	2700-6500
KIN/400*/**	400	120/150	30°/60°/90°/80°x140°	2700-6500

* **Beam Angle:** 30° (030) / 60° (060) / 90° (090) / 80°x140° (814)

** **Colour Temperature:** 2000-3000K (02) / 4000K (04) / 6000K (06)

*** **Lumen:** 120lm/W - (12) / 150lm/W - 15

Emergency Back-up Option Available on 75W, 100W, 120W, 150W, 200W, 300W.


Emergency Back-Up Time = 90 minutes at 20% Power

DIMENSIONAL DATA


	35W/50W 75W/100W	120W/150W	200W	300W/400W
Length	310mm	365mm	420mm	420mm
Width	365mm	365mm	365mm	730mm
Height	60mm	60mm	60mm	60mm
Weight	4.5kg	5kg	6kg	12kg

ILLUMINATION DATA


30 Degree



60 Degree



90 Degree



80x140 Degree

